

Avide LED Flood Light Slim 50W NW 4000K

Product code: ABSFLNW-50W
Brand link: avidelighting.com/qr/ABSFLNW-50W
ID: AB-190518
Company name: Bramcke Hungary Kft.
Company address: Kishatár utca 17., 4031 Debrecen

QR code:



Date of issue: 2024-05-03

Page: 1/3

SPECIFICATIONS

EAN code: 5999562284384
Warranty: 3year(s)
Working temperature: -20 - +40 °C
Packaging: 1/b 5/c 225/p
Certifications: CE

TECHNICAL DETAILS

Wattage: 50W
Voltage: 85-265V
Beam angle: 120°
Dimmability: No
Lumen output: 3 000lm
Color temperature: 4 000K
Lifetime: 25 000h
Energy class: G
Type of LED: COB
Driver: CCD
CRI: >80
IP standard: IP65

BOX PICTURE



Avide LED Flood Light Slim 50W NW 4000K

Product code: ABSFLNW-50W
Brand link: avidelighting.com/qr/ABSFLNW-50W
ID: AB-190518
Company name: Bramcke Hungary Kft.
Company address: Kishatár utca 17., 4031 Debrecen



Date of issue: 2024-05-03
Page: 2/3

PRODUCT SIZE

Width: 240mm
 Height: 285mm
 Depth: 60mm

CARDBOARD BOX

EAN: 5999562284384
 Packaging: 1/b 5/c 225/p
 Dimensions: 245mm x 65mm x 310mm
 Net weight: 1 548.8g
 Gross weight: 1 600g

CARTON

EAN: 5999562284421
 Packaging: 1/b 5/c 225/p
 Dimensions: 345mm x 260mm x 330mm
 Net weight: 7.744kg
 Gross weight: 8kg


PALLET EXAMPLE

Height:
 Width: 120cm (std Euro pallet)
 Mepth: 80cm (std Euro pallet)
 Cartons per pallet: 45carton/pallet
 Cartons per row: 9pcs
 Net weight: 348.48kg
 Gross weight: 360kg

PRODUCT PICTURE



PRODUCT OUTLINE



Avide LED Flood Light Slim 50W NW 4000K

Product code:	ABSFLNW-50W
Brand link:	avidelighting.com/qr/ABSFLNW-50W
ID:	AB-190518
Company name:	Bramcke Hungary Kft.
Company address:	Kisatár utca 17., 4031 Debrecen



Date of issue: 2024-05-03

Page: 3/3

PRODUCT DESCRIPTION

The battery-operated Avide COB LED floodlights enable portable, mobile use. Brightness is adjustable in two stages. They can provide the same brightness as traditional halogen floodlights but with much lower power consumption; thus when operated from a battery, they can ensure a longer operating time. The battery of the floodlight can be fully charged in 3 hours and with one full charge it can operate for up to 5 hours. COB (chip-on-board) represents one of the most recent LED technologies, focusing the emitted light much better and thus providing better lighting at a longer distance. LED floodlights can provide up to 20 times longer lifetime compared to products using traditional light bulbs. Due to its IP65 classification, it is perfectly suitable for both indoor and outdoor use. The edge of the floodlight features a metal frame that makes it possible to be turned and tilted, thus enabling you to adjust the adequate lighting angle.

The LED floodlights are sold with a 30 cm long cable end and the plug is not included in the package! The product may only be installed by a professional! Any operation with the power on carries the hazard of an electric shock.

The Avide COB Floodlights are available in neutral white (NW) / cold white (CW) color temperatures in 10W / 20W / 30W / 50W / 80W / 100W / 150W power output versions. The "SLIM" design is also available in neutral white (NW) / cold white (CW) color temperatures and a 10W / 20W / 30W / 50W power output.