Datasheet and description



Avide LED Flood Light Slim SMD 20W NW 4000K White

Product code: ABSSFLNW-20W-W

Brand link: avidelighting.com/qr/ABSSFLNW-20W-W

ID: AB-190518

Company name: Bramcke Hungary Kft.

Company address: Kishatár utca 17., 4031 Debrecen



Date of issue: 2024-04-23

Page: 1/3

SPECIFICATIONS

EAN code: 5999097924861

Warranty: 3year(s)

-20 - +40 °C Working temperature: Packaging: 1/b 40/c 1200/p

CE Certifications:

TECHNICAL DETAILS

20W Wattage:

Voltage: 220-240V 120° Beam angle:

Dimmability: No

Lumen output: 2 000lm Color temperature: 4 000K Lifetime: 25 000h

F Energy class: SMD

Type of LED:

Driver:

CRI: >80 IP standard: IP65

BOX PICTURE



Datasheet and description



Avide LED Flood Light Slim SMD 20W NW 4000K White

Product code: ABSSFLNW-20W-W

Brand link: avidelighting.com/qr/ABSSFLNW-20W-W

ID: AB-190518

Company name: Bramcke Hungary Kft.

Company address: Kishatár utca 17., 4031 Debrecen



Date of issue: 2024-04-23

Page: 2/3

PRODUCT SIZE

Width: 112mm
Height: 77mm
Depth: 33mm

CARDBOARD BOX

EAN: 5999097924861 Packaging: 1/b 40/c 1200/p

Dimensions: 95mm x 135mm x 50mm

Net weight: 307.3g Gross weight: 317.5g

CARTON

EAN: 5999097924878 Packaging: 1/b 40/c 1200/p

Dimensions: 550mm x 320mm x 220mm

Net weight: 12.2936kg Gross weight: 12.7kg

PALLET EXAMPLE

Height:

Width: 120cm (std Euro pallet)

Mepth: 80cm (std Euro pallet)

Cartons per pallet: 30carton/pallet


Cartons per row:

Net weight: 368.808kg
Gross weight: 381kg

PRODUCT PICTURE



PRODUCT OUTLINE



Datasheet and description



Avide LED Flood Light Slim SMD 20W NW 4000K White

Product code: ABSSFLNW-20W-W

Brand link: avidelighting.com/qr/ABSSFLNW-20W-W

ID: AB-190518

Company name: Bramcke Hungary Kft.

Company address: Kishatár utca 17., 4031 Debrecen



Date of issue: 2024-04-23

Page: 3/3

PRODUCT DESCRIPTION

The Avide SMD LED floodlights can provide the same brightness as traditional halogen lights but with a much lower power consumption, thus significant savings can be realized with their use. LED floodlights provide up to 20 times longer lifetime compared to products using traditional light bulbs. With their IP65 classification, they are also perfectly suitable for outdoor use. The edge of the floodlight features a movable metal frame, thus you can fix it on the ground, the wall or even the ceiling. After mounting, the angle can be adjusted anytime, thus it will provide the light you need exactly where you need it.

The LED floodlights are sold with a 30 cm long cable end and the plug is not included in the package! The product may only be installed by a professional! Any operation with the power on carries the hazard of an electric shock.

The Avide SMD floodlights are available in neutral white (NW) / cold white (CW) color temperatures in 10W / 20W / 30W / 50W power output versions, as well as in a neutral white (NW) color temperature and a 100W / 150W / 200W power output.