Datasheet and description



Avide LED Downlight 38° Square 7W NW 4000K

Product code: ALDLS38NW-S-7W

Brand link: avidelighting.com/qr/ALDLS38NW-S-7W

ID: AB-190518

Company name: Bramcke Hungary Kft.

Company address: Kishatár utca 17., 4031 Debrecen



Date of issue: 2024-05-06

Page: 1/3

SPECIFICATIONS

EAN code: 5999097916125

Warranty: 3year(s)

Material: PC+PC

Working temperature: -20 -+40°c

Packaging: 1/b 100/c 1600/p

Certifications: CE

TECHNICAL DETAILS

Wattage: 7W

Voltage: 100-265V

Beam angle: 38°

Dimmability: No

Lumen output: 677lm

Color temperature: 4 000K

Lifetime: 20 000h

Energy class:

Type of LED: SMD2835
IP standard: IP20

BOX PICTURE



Datasheet and description



Avide LED Downlight 38° Square 7W NW 4000K

Product code: ALDLS38NW-S-7W

Brand link: avidelighting.com/qr/ALDLS38NW-S-7W

ID: AB-190518

Company name: Bramcke Hungary Kft.

Company address: Kishatár utca 17., 4031 Debrecen



Date of issue: 2024-05-06

Page: 2/3

PRODUCT SIZE

Diameter: 90mm
Height: 90mm
Cut out size: 75-85mm

CARDBOARD BOX

EAN: 5999097916125 Packaging: 1/b 100/c 1600/p

Dimensions: 125mm x 105mm x 53mm

Net weight: 66g Gross weight: 81g

CARTON

EAN: 5999097916132 Packaging: 1/b 100/c 1600/p


Dimensions: 640mm x 290mm x 440mm

Net weight: 6.6kg
Gross weight: 8.1kg

PRODUCT PICTURE



PRODUCT OUTLINE



PALLET EXAMPLE

Height:

Width: 120cm (std Euro pallet)
Mepth: 80cm (std Euro pallet)

Cartons per pallet: 16carton/pallet

Cartons per row:

Net weight: 105.6kg Gross weight: 129.6kg

Datasheet and description



Avide LED Downlight 38° Square 7W NW 4000K

Product code: ALDLS38NW-S-7W

Brand link: avidelighting.com/qr/ALDLS38NW-S-7W

ID: AB-190518

Company name: Bramcke Hungary Kft.

Company address: Kishatár utca 17., 4031 Debrecen



Date of issue: 2024-05-06

Page: 3/3

PRODUCT DESCRIPTION

The Avide spot lamps can be recessed into suspended ceilings and can be fixed easily. The internal part of the frame can be tilted, thus the light of the installed lamp can be directed in the preferred angle for maximum light utilization. Its light is directed, emitting light at an angle of 38 ° in a focused way. Also ideal for lighting narrower spaces, including kitchen counters and cabinets with a mirror. Available both in round and square form.