Datasheet and description



Avide LED Glass Tube 18W G13 1200mm NW 4000K 120lm/W

Product code: AB1200T8-18W-NW-GL-IL

Brand link: avidelighting.com/qr/AB1200T8-18W-NW-GL-IL

ID: AB-190518

Company name: Bramcke Hungary Kft.

Company address: Kishatár utca 17., 4031 Debrecen



Date of issue: 2024-04-23

Page: 1/3

SPECIFICATIONS

EAN code: 5999097925509

Warranty: 2year(s)
Working temperature: -20 - +40°C
Packaging: $1/b \ 25/c \ 600/p$

Certifications: CE

PRODUCT PICTURE



TECHNICAL DETAILS

Wattage: 18W

Voltage: 180-265V Beam angle: 240°

Dimmability: No

Lumen output: 2 160lm
Color temperature: 4 000K
Lifetime: 25 000h

Energy class: A+

Type of LED: SMD

IP standard: IP20

Datasheet and description



Avide LED Glass Tube 18W G13 1200mm NW 4000K 120lm/W

Product code: AB1200T8-18W-NW-GL-IL

Brand link: avidelighting.com/qr/AB1200T8-18W-NW-GL-IL

ID: AB-190518

Company name: Bramcke Hungary Kft.

Company address: Kishatár utca 17., 4031 Debrecen



Date of issue: 2024-04-23

Page: 2/3

PRODUCT SIZE

Diameter: 26mm
Length: 1 200mm

CARDBOARD BOX

EAN: 5999097925509 Packaging: 1/b 25/c 600/p

Dimensions: 1 260mm x 32mm x 32mm

Net weight: 176g Gross weight: 232g

CARTON

EAN: 5999097925516 Packaging: 1/b 25/c 600/p

Dimensions: 1 270mm x 190mm x 195mm

Net weight: 4.4kg Gross weight: 5.8kg

PALLET EXAMPLE

Height:

Width: 120cm (std Euro pallet)

Mepth: 80cm (std Euro pallet)

Cartons per pallet: 24carton/pallet

Cartons per row:

Net weight: 105.6kg Gross weight: 139.2kg

PRODUCT PICTURE

PRODUCT OUTLINE

Datasheet and description



Avide LED Glass Tube 18W G13 1200mm NW 4000K 120lm/W

Product code: AB1200T8-18W-NW-GL-IL

Brand link: avidelighting.com/qr/AB1200T8-18W-NW-GL-IL

ID: AB-190518

Company name: Bramcke Hungary Kft.

Company address: Kishatár utca 17., 4031 Debrecen



Date of issue: 2024-04-23

Page: 3/3

PRODUCT DESCRIPTION

The Avide LED dust- and moisture-proof fixtures for tubes represent the energy-saving versions of traditional fittings. The fixtures of different lengths replacing the tube fixtures have a built-in LED panel that guarantees energy-saving operation. In terms of the material used, the products have a break-resistant cover. Due to the IP65 protection of the fixture, it is protected from dust and moisture, thus can also be operated at places with higher exposure to dust and humidity.

The product range includes a 1 and 2 LED design, in lengths of 0.6, 1.2 and 1.5 meter lengths, with a transparent cover.

OUR IP protected fixture category includes numerous additional products. Learn more about these on the following link.