

Avide LED Flood Light Slim SMD 10W with Stand 1.5m NW 4000K

Product code:	ABSSTFLNW-10W
Brand link:	avidelighting.com/qr/ABSSTFLNW-10W
ID:	AB-190518
Company name:	Bramcke Hungary Kft.
Company address:	Kisatár utca 17., 4031 Debrecen



Date of issue: 2024-05-08

Page: 1/3

SPECIFICATIONS

EAN code:	5999097919300
Warranty:	3year(s)
Working temperature:	-20 - +50°C
Packaging:	1/b 10/c 480/p
Certifications:	CE

TECHNICAL DETAILS

Wattage:	10W
Voltage:	AC180-240V
Beam angle:	120°
Dimmability:	No
Lumen output:	1 000lm
Color temperature:	4 000K
Lifetime:	30 000h
Energy class:	F
Type of LED:	SMD
Driver:	
CRI:	>70
IP standard:	IP65

BOX PICTURE



Avide LED Flood Light Slim SMD 10W with Stand 1.5m NW 4000K

Product code: ABSSTFLNW-10W
Brand link: avidelighting.com/qr/ABSSTFLNW-10W
ID: AB-190518
Company name: Bramcke Hungary Kft.
Company address: Kishatár utca 17., 4031 Debrecen

QR code:



Date of issue: 2024-05-08

Page: 2/3

PRODUCT SIZE

Width: 130mm
Height: 192mm
Depth: 100mm

CARDBOARD BOX

EAN: 5999097919300
Packaging: 1/b 10/c 480/p
Dimensions: 193mm x 210mm x 75mm
Net weight: 566.3g
Gross weight: 585g

CARTON

EAN: 5999097919317
Packaging: 1/b 10/c 480/p
Dimensions: 395mm x 395mm x 230mm
Net weight: 5.6628kg
Gross weight: 5.85kg

PALLET EXAMPLE

Height:
Width: 120cm (std Euro pallet)
Mepth: 80cm (std Euro pallet)
Cartons per pallet: 48carton/pallet
Cartons per row:
Net weight: 271.8144kg
Gross weight: 280.8kg

PRODUCT PICTURE



PRODUCT OUTLINE

Avide LED Flood Light Slim SMD 10W with Stand 1.5m NW 4000K

Product code: ABSSTFLNW-10W
Brand link: avidelighting.com/qr/ABSSTFLNW-10W
ID: AB-190518
Company name: Bramcke Hungary Kft.
Company address: Kishatár utca 17., 4031 Debrecen

QR code:



Date of issue: 2024-05-08

Page: 3/3

PRODUCT DESCRIPTION

Light your work area with the Avide SMD portable LED floodlights. LED floodlights can provide up to 20 times longer lifetime compared to products using traditional light bulbs. Due to its IP65 classification, it is perfectly suitable for both indoor and outdoor use. The edge of the floodlight features a metal frame that makes it possible to be turned and tilted, thus enabling you to adjust the adequate lighting angle.

Do not look directly into the floodlight! Do not use the fixture under water!

Due to its portability, you can take it where an extra light source is needed the most. The 3G0.75 type and 1.5-meter-long power cable provides convenient access to the power source.

The Avide SMD Floodlights are available in a neutral white (NW) color temperature and 10W, 20W, 30W and 50W power output versions.